

# DOOH960

**Outdoor scale.  
Service from either side.**

960 × 960 mm cabinets for outdoor display installations.



**Outdoor display**

# Plan access from the start



## Front and rear maintenance

Module access from either side gives more options when planning the complete display structure.

## P8 soft-mask option

A soft protective mask is available for P8. P6.67 and P10 use their corresponding standard configurations.

# Configuration at a glance

| Configuration   | P6.67            | P8        | P10           |
|-----------------|------------------|-----------|---------------|
| Cabinet pixels  | 144 × 144        | 120 × 120 | 96 × 96       |
| W × H × D / mm  | 960 × 960 × 92   |           |               |
| Weight          | 24.5 kg          |           |               |
| Soft mask       | Not available    | Optional  | Not available |
| Refresh options | 3,840 / 7,680 Hz |           |               |

IP66. Optional curved corner configuration depends on the project.

# Plan your DOOH960 project

## Project context

Share the outdoor location, screen size and viewing distance.

## Technical needs

Confirm the mounting design, service side and soft-mask requirement.

## Details to confirm

Specify ambient light, operating schedule and electrical supply.

[led@turingled.com](mailto:led@turingled.com) / [WhatsApp +86 15014067656](https://www.whatsapp.com/channel/0029915014067656)