

HoloPoster COB

Transparent content in a framed format.

COB Holo Mesh display sizes for retail
and exhibition layouts.

Transparent display terminal



An open-view display terminal

A transparent surface

P3.91 and P6.25 offer different levels of image detail and transmittance within the framed display family.

Frame and installation

The complete assembly includes the frame and support structure. Confirm floor-standing or suspended use for the selected model.

Installation details follow the selected configuration and site layout.

Configuration at a glance

Parameter	P3.91	P6.25
Transmittance	70%	90%
Peak power / W/m ²	600	550
Average power / W/m ²	150	135
Refresh rate	≥3,840 Hz	
Protection	IP43	

Power consumption varies with content and operating settings. Confirm the installation environment.

Display area and overall dimensions

Display W × H / mm	Overall W × H / mm
1,000 × 2,000	1,008 × 2,449
1,000 × 2,400	1,008 × 2,849
2,000 × 2,000	2,008 × 2,449
2,000 × 2,400	2,008 × 2,849

Allow additional site space for support, cable routing and access.

Plan your HoloPoster COB project

Project context

Share the space dimensions, viewing distance and ambient light conditions.

Technical needs

Choose the display area and confirm the overall frame and support size.

Details to confirm

Provide the content source, cable route and installation method.

led@turingled.com / WhatsApp +86 15014067656